

# VisiJet<sup>®</sup> PXL Colors Revision Date: 19 June 2013

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

## 1.1 Identification of the substance or preparation: VisiJet<sup>®</sup> PXL Colors (clear, cyan, magenta, yellow, black)

1.2 Use of the substance / preparation: For use with ProJet® x60 3D printers

#### 1.3 Company/undertaking identification:

3D Systems, Inc. 333 Three D Systems Circle Rock Hill, South Carolina U.S.A. Phone: 803.326.3900 or Toll-free Phone: 800.793.3669 800.424.9300 - Chemtrec

3D Systems Europe Ltd. Mark House, Mark Road Hemel Hempstead Herts HP2 7 United Kingdom Phone: +44 144-2282600 703.527.3887 - Chemtrec (U.S.)

#### 2. HAZARDS IDENTIFICATION

2.1 Classification: Not classified according to GHS, Regulation (EC) No. 1272/2008, HazCom 2012.

2.2 Label Elements Regulation (EC) No, 1272/2008:

Hazard pictograms and signal word: None

Hazard statements: None



**NFPA** Ratings 0 = Minimal 1 = Slight2 = Moderate3 = Serious

4 = Severe

Hazardous Materials Identification System (HMIS): (Degree of hazard: 0 = low,

4 = extreme);Health 0 Flammability 0 Physical Hazards 0

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Preparation related information

Description: aqueous solution

3.2 Hazard ingredients:

Chemical name	CAS-No	EC-No	%	Classification	
				Regulation (EC) 1272/2008	Regulation 67/548/EEC, 1999/45/EC
2-pyrrolidone	616-45-5	210-483-1	0-1	Xi R22, 37/38,41	Acut. Tox. 4, H302, STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam.1, H318



# VisiJet<sup>®</sup> PXL Colors

Revision Date: 19 June 2013

#### 4. FIRST AID MEASURES

**4.1 In case of inhalation:** Move affected person to fresh air. If respiratory irritation occurs, seek medical attention immediately.

4.2 In case of skin contact: Flush skin with plenty of soap and water.

4.3 In case of eye contact: Flush eyes with plenty of water.

4.4 In case of ingestion: If ingested, drink plenty of water. Do not induce vomiting.

#### **5. FIRE-FIGHTING MEASURES**

5.1. Suitable extinguishing media: Water mist, dry chemical, carbon dioxide, or appropriate foam.

**5.2.** Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases: Thermal decomposition products can include CO<sub>2</sub>, CO and nitrogen oxides.

#### 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions: Wear appropriate protective equipment and clothing.

6.2. Environmental precautions: Avoid discharge to sewer system.

6.3. Methods for cleaning up: Wipe up. Place all waste in an appropriate container for disposal.

#### 7. HANDLING AND STORAGE

7.1 Handling: Avoid contact with skin and eyes. Do not allow to enter drains or watercourses.

7.2 Storage: Store sealed in the original container at room temperature.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### 8.1 Exposure limit values:

General Product Information: No occupational exposure limits (PEL/TWA) have been established for this product. Component Analysis:

Component	Component Manufacturer IEL (Internal Exposure Limit)
2-pyrrolidone	NA

#### 8.2 Exposure controls

Technical measures to prevent exposure: Use local exhaust ventilation.

**Instructual measures to prevent exposure:** When using, do not eat, drink or smoke. Wash hands after handling and before eating, smoking and using the lavatory and at the end of the day.

Personal protection equipment:

**Respiratory protection:** If ventilation cannot effectively keep vapor concentrations below established limits, appropriate certified respiratory protection must be provided (respiratory mask FFP3).

Hand protection: Use impervious nitrile gloves.

Eye protection: Wear safety glasses or chemical goggles.

Body protection: Use apron and closed shoes.



# VisiJet<sup>®</sup> PXL Colors

Revision Date: 19 June 2013

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Appearance:

Physical state: Liquid (clear, cyan, magenta, yellow or black)

#### 9.2 Important health, safety and environmental information

pH (20 °C): Melting point/range (°C): Boiling point/range (°C): Flash point (°C): Ignition temperature (°C): Vapour pressure (°C): Density (g/cm3): Bulk density (kg/m3): Water solubility (20 °C in g/l):	9.8 0° 100 NA NA 1.0 NA soluble
Bulk density (kg/m3): Water solubility (20°C in g/l): Viscosity, dynamic (mPa s): Dust explosion hazard: Explosion limits:	

#### **10. STABILITY AND REACTIVITY**

Hazardous decomposition products: Carbon dioxide, carbon monoxide and other toxic fumes can be released at high temperatures or upon burning.

#### 11. TOXICOLOGICAL INFORMATION

#### 11.1 Toxicokinetics, metabolism and distribution: NA

#### 11.2 Acute effects (toxicity tests)

Component	LD50 Oral	LD <sub>50</sub> Dermal
2-pyrrolidone	328 mg/kg (rats)	NA

#### 11.3 General remarks:

Carcinogenicity: None of this product's components are listed by ACGIH, IARC, OSHA, NIOSH, or NTP.

#### 12. Ecological information

**12.1 Ecotoxicity:** The aquatic toxicity of the product is unknown. No data are available for the components of this product.

12.2 Mobility: No information available for product.

12.3 Persistence and degradability: No information available for product.

12.4 Results of PBT assessment: No information available for product

12.5 Other adverse effects: No information available for product

### **13. DISPOSAL CONSIDERATIONS**

**Appropriate disposal** / **Product:** Do not contaminate drains, soil or surface waters with this material or its container. Reduce waste by attempting to utilize product completely. Dispose of this container and its contents in accordance with all local, state, and federal regulations.



# VisiJet<sup>®</sup> PXL Colors

Revision Date: 19 June 2013

#### **14. TRANSPORT INFORMATION**

14.1 Land transport (ADR/RID/GGVSE): Not regulated

14.2 Sea transport (IMDG-Code/GGVSee): Not regulated

14.3 Air transport (ICAO-IATA/DGR): Not regulated

#### **15. REGULATORY INFORMATION**

#### 15.1 EU regulations

EINEC/ELINCS/NLP: All materials are listed REACH Annex XVII: None listed

#### 15.2. US FEDERAL

TSCA: All materials are listed on the TSCA Inventory or are not subject to TSCA requirements: California Proposition 65: This product does not contain chemicals which are known to the state of California to cause cancer, birth, or any other reproductive defects.

#### **16. OTHER INFORMATION**

# 16.1 Relevant Hazard Statements (number and full text) referred to in sections 2 and 3 (according to (EC) No. 1272/2008):

Acute Tox.4, H302: Acute Toxicity, category 4, H 302: Harmful if swallowed STOT SE 3, H335: Specific target organ toxicity-single exposure, category 3 : May cause respiratory irritation Skin Irrit. 2, H315: Skin irritation, category 2, H315: Causes skin irritation Eye Dam.1, H318: Eye Damage, category 1, H318: Causes serious eye damage

#### Relevant R-Phrases (number and full text) referred to in sections 2 and 3:

Xi: Irritant R22: Harmful if swallowed R37/38: Irritating to respiratory system and skin R41: Risk of serious damage to eyes

SDS Creation Date:......March 22, 2013 SDS Revision #:.....B SDS Revision Date:.....June 19, 2013 Reason for Revision:.....Update product use.

#### www.3dsystems.com

800.793.3669 (Toll-free in the US GMT-07:00; N. America, Mon – Fri, 6:00 a.m. to 6 p.m.) 803.326.3900 (Outside the U.S. GMT-07:00; N. America, Mon – Fri, 6:00 a.m. to 6 p.m.) +44 144-2282600 (Europe GMT+01:00; Mon – Fri, 08:00 a.m. - 17:00 p.m. MEZ)

DISCLAIMER OF LIABILITY: The following supersedes any related provision in your company's forms, letters, and agreements from, by or with 3D Systems Corporation. 3D Systems, Inc. makes no warranty whether expressed or implied, including warranties of merchantability or of fitness for a particular purpose for this product. No statements or recommendations contained in the product literature are to be construed as inducements to infringe any relevant patent now or hereafter in existence. Under no circumstances shall 3D Systems, Inc. be liable for incidental, consequential, or other damages from alleged negligence, breach of warranty, strict liability or any other theory, arising out of the use or handling of this product. The sole liability of 3D Systems, Inc. for any claims arising out of the manufacture, use or sale of its product shall be for the buyer's purchase price.

The contents of this safety data sheet are subject to change without notice. 3D Systems, Inc. recommends that you periodically check <u>www.3dsystems.com</u> to make sure you are using the most current safety data sheet.

© Copyright 2013 by 3D Systems, Inc. All rights reserved. The 3D logo, VisiJet and ProJet are registered trademarks of 3D Systems, Inc.